

### PH213 - 3000 PSI

**Applicable Standard :** ISO 18752 - AC (DN06 - 25) , ISO 18752 - BC & CC (DN31 - 51)



### Construction

- Inner tube** Black colour, synthetic rubber resistant to oil and water
- Reinforcement** Single steel wire braid (DN06 - 12)  
Double steel wire braids (DN16 - 25)  
Four high tensile steel wire spirals (DN31 - 51)
- Cover** Black colour, synthetic rubber resistant to abrasion and weather, oil & ozone. smooth \*and wrap finish applicable only for wire braided hose
- Application** Constant pressure hydraulic lines 210 bar for use with petroleum or water based fluids in hydraulic systems. Suitable for Agricultural, Construction & material handling equipments / systems

Cover Options
PH213:MSHA
PH223: HARDX MSHA
PH403 : ABRAZONX MSHA
Temperature Usage Options
PH413: -55°C to + 100°C (WB)
PH433: -40°C to +135°C MSHA (WB)
PH453: : -40°C to +153°C MSHA (WB)

**Note :** WB: Wire Braid; WS: Wire Spiral

Item Code	Dash Size	DN	Hose Structure	ID		OD		WP		BP		BR/r		W
				inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH213-04	-04	06	1WB	1/4	6.7	0.50	12.8	3000	210	12000	840	2.0	50	0.216
PH213-05	-05	08	1WB	5/16	8.2	0.56	14.3	3000	210	12000	840	2.2	55	0.242
PH213-06	-06	10	1WB	3/8	9.8	0.64	16.3	3000	210	12000	840	2.6	65	0.303
PH213-08	-08	12	1WB	1/2	13.1	0.80	20.3	3000	210	12000	840	3.5	90	0.446
PH213-10	-10	16	2WB	5/8	16.2	0.93	23.5	3000	210	12000	840	3.9	100	0.736
PH213-12	-12	19	2WB	3/4	19.3	1.10	28.0	3000	210	12000	840	4.7	120	0.994
PH213-16	-16	25	2WB	1	25.9	1.48	37.5	3000	210	12000	840	5.9	150	1.449
PH213-20	-20	31	4WS	1.1/4	32.2	1.85	47.0	3000	210	12000	840	8.3	210	2.822
PH213-24	-24	38	4WS	1.1/2	38.7	2.11	53.5	3000	210	12000	840	22.0	560	3.566
PH213-32	-32	51	4WS	2	51.3	2.56	65.0	3000	210	12000	840	27.6	700	5.132



**Temperature Range :** WB -40°C to +100°C, WS -40°C to +120°C

**Intermittent :** +120°C

\*Smooth cover available only upto size 1"