

**PH290 - PILOT HOSE**



**Construction**

- Inner tube** Black colour, synthetic rubber resistant to oil and water
- Reinforcement** Single steel wire braid
- Cover** Black colour, synthetic rubber resistant to abrasion and weather, oil & ozone. Available in Wrap and Smooth finish\*
- Application** Medium Pressure hydraulic lines 105 bar and requires compact outer dia. For use with petroleum based fluids, water based fluids in Hydraulic systems. Suitable for Agricultural, Earth Moving & material handling equipment and machineries/systems

Cover Options
PH290 : MSHA
PH492 : HARDX MSHA

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH290-04	-04	06	1/4	6.4	0.44	11.2	1525	105	6020	415	1.2	30	0.169
PH290-05	-05	08	5/16	8.0	0.50	12.8	1525	105	6020	415	1.4	35	0.193
PH290-06	-06	10	3/8	9.5	0.56	14.3	1525	105	6020	415	2.0	50	0.272
PH290-08	-08	12	1/2	12.7	0.69	17.4	1525	105	6020	415	2.4	60	0.294



**Temperature Range** : Continuous: -40°C to +100°C

**Intermittent** : +120°C

\*Smooth cover available only upto size 1"