

PH443 - FUEL DISPENSING - SOFT WALL

Applicable Standard : EN 1360 Type 1



Construction

- Inner tube** Black colour, Synthetic rubber resistant to petrol and diesel fuel
- Reinforcement** Double Textile braid
- Cover** Black Colour, synthetic rubber resistant to fuel and weather. Available in Wrap and Smooth finish*, Colour option Blue and Green available on request.
- Application** Petrol and diesel fuel dispensing lines of pressure 235 psi

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH443-08	-08	12	1/2	12.5	0.91	23.0	235	16	700	48	2.4	60	0.385
PH443-10	-10	16	5/8	16.0	1.02	26.0	235	16	700	48	3.1	80	0.396
PH443-12	-12	19	3/4	19.0	1.14	29.0	235	16	700	48	3.9	100	0.450
PH443-13	-13	21	7/8	22.0	1.22	31.0	235	16	700	48	5.1	130	0.565
PH443-16	-16	25	1	25.0	1.38	35.0	235	16	700	48	5.9	150	0.571



Temperature Range : Continuous: -30°C to +55°C

Electrical resistance max : 1 X 10² ohms

*Smooth cover available only upto size 1"