

PH514 - PW 4K - 1 WB



Construction

- Inner tube** Black colour, Synthetic rubber resistant to hot water
- Reinforcement** Single steel wire braid
- Cover** Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone. Available in wrap and smooth finish*
- Application** For pressure washer applications with a maximum pressure of 280 Bar. For cold and hot water up to 155 °C

Note : Also Available in Blue and Grey colour Covers on request, Not suitable for steam and oil applications

| Item Code | Dash Size | DN | ID | | OD | | WP | | BP | | BR/r | | W |
|-----------|-----------|----|------|------|------|------|------|-----|-------|-----|------|-----|-------|
| | | | inch | mm | inch | mm | psi | bar | psi | bar | inch | mm | kg/m |
| PH514-04 | -04 | 06 | 1/4 | 6.7 | 0.47 | 12.0 | 4000 | 280 | 12000 | 830 | 1.4 | 35 | 0.194 |
| PH514-05 | -05 | 08 | 5/16 | 8.2 | 0.54 | 13.7 | 4000 | 280 | 12000 | 830 | 2.6 | 65 | 0.235 |
| PH514-06 | -06 | 10 | 3/8 | 9.8 | 0.63 | 16.0 | 4000 | 280 | 12000 | 830 | 3.0 | 75 | 0.305 |
| PH514-08 | -08 | 12 | 1/2 | 13.1 | 0.77 | 19.6 | 4000 | 280 | 12000 | 830 | 3.9 | 100 | 0.425 |

 **Temperature Range :** Continuous: -10°C to +155°C

***Smooth cover available only upto size 1"**