

PH622 - HIGH PRESSURE PLASTER SPRAY HOSE



Construction

- Inner tube** Black colour, Synthetic and natural rubber blend resistant to abrasion
- Reinforcement** Plies of synthetic textile cords
- Cover** Black colour, Synthetic rubber resistant to ozone, weather and abrasion
- Application** For High Pressure Cement/ Plaster Spraying in construction industry

Item Code	Dash Size	ID		OD		WP		BP		kg/m
		inch	mm	inch	mm	psi	bar	psi	bar	
PH622-16	-16	1	25.0	1.54	39.0	580	40	1740	120	0.93
PH622-20	-20	1.1/4	32.0	1.81	46.0	580	40	1740	120	1.15
PH622-24	-24	1.1/2	38.0	2.13	54.0	580	40	1740	120	1.60
PH622-32	-32	2	51.0	2.72	69.0	580	40	1740	120	2.50
PH622-40	-40	2.1/2	64.0	3.39	86.0	580	40	1740	120	3.00
PH622-48	-48	3	76.0	3.86	98.0	580	40	1740	120	4.20
PH622-64	-64	4	102.0	5.12	130.0	580	40	1740	120	5.60
PH622-80	-80	5	127.0	6.18	157.0	580	40	1740	120	6.00



Temperature Range : Continuous: -30°C to +70°C