

### PH341 - PAINT & AGGRESSIVE CHEMICAL SPRAY - 1W



### Construction

- Inner tube** PTFE (Polytetrafluoroethylene)
- Reinforcement** Single Braid of steel wire
- Cover** Polyurethane, Blue Colour, Pin pricked

**Application** Airless paint spray systems for 200 to 350 bar. Suitable for applications requiring chemical resistance to solvents and aggressive fluids. Specially suitable for moisture cure adhesives and two components chemicals transfer

**Note :** Special colours available on request

| Item Code | Dash Size | DN | ID   |      | OD    |      | WP   |     | BP    |      | BR/r |    | W   |
|-----------|-----------|----|------|------|-------|------|------|-----|-------|------|------|----|-----|
|           |           |    | inch | mm   | inch  | mm   | psi  | bar | psi   | bar  | inch | mm | g/m |
| PH341-03  | -03       | 05 | 3/16 | 4.8  | 0.380 | 9.7  | 5000 | 350 | 20000 | 1400 | 1.2  | 30 | 138 |
| PH341-04  | -04       | 06 | 1/4  | 6.4  | 0.460 | 11.7 | 4650 | 320 | 18600 | 1280 | 1.6  | 40 | 180 |
| PH341-05  | -05       | 08 | 5/16 | 8.0  | 0.535 | 13.6 | 4000 | 275 | 16000 | 1100 | 2.0  | 50 | 220 |
| PH341-06  | -06       | 10 | 3/8  | 9.5  | 0.595 | 15.1 | 3600 | 250 | 14400 | 1000 | 2.4  | 60 | 257 |
| PH341-08  | -08       | 12 | 1/2  | 12.7 | 0.725 | 18.4 | 2900 | 200 | 11600 | 800  | 3.0  | 75 | 337 |



**Temperature Range :** Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids