

PH460 ROCKDRILL

Construction

- Inner tube** Black colour, synthetic rubber resistant to air.
- Reinforcement** Single steel wire braid
- Cover** Black colour, synthetic rubber resistant to weather, abrasion & ozone.
- Application** Compressed air service in severe working conditions in mines, quarries and industrial applications



| Item Code | Dash Size | DN | ID | | OD | | WP | | BP | | BR/r | | W |
|-----------|-----------|----|-------|------|------|------|------|-----|------|-----|-------|-----|-------|
| | | | inch | mm | inch | mm | psi | bar | psi | bar | inch | mm | kg/m |
| PH 460-08 | -08 | 12 | 1/2 | 13.1 | 0.79 | 20 | 1160 | 80 | 3480 | 240 | 7.87 | 200 | 0.385 |
| PH 460-12 | -12 | 19 | 3/4 | 19.3 | 1.14 | 29 | 870 | 60 | 2610 | 180 | 9.45 | 240 | 0.675 |
| PH 460-16 | -16 | 25 | 1 | 25.9 | 1.4 | 35.5 | 725 | 50 | 2175 | 150 | 11.81 | 300 | 0.777 |
| PH 460-20 | -20 | 31 | 1.1/4 | 32.4 | 1.65 | 42 | 725 | 50 | 2175 | 150 | 16.54 | 420 | 0.976 |
| PH 460-24 | -24 | 38 | 1.1/2 | 38.7 | 2.04 | 51.7 | 600 | 40 | 1740 | 120 | 19.69 | 500 | 1.337 |
| PH 460-32 | -32 | 51 | 2 | 51.3 | 2.48 | 63 | 600 | 40 | 1740 | 120 | 24.8 | 630 | 1.783 |



Temperature Range : Continuous: -40°C to +90°C

*Smooth cover available only upto size 1"