


PH684 - SHOT BLASTING HOSE W.P. 12 BAR

Construction

- Inner tube** Black Colour, Synthetic and natural rubber blend resistant to abrasion
- Reinforcement** Four Plies of synthetic textile cords with two cross anti static copper wires
- Cover** Black colour, Synthetic rubber resistant to ozone, weather and abrasion
- Application** Suitably designed long lasting heavy duty hose for use in sand , metal grits and foundry waste with conductive rubber compound to ensure static electricity dissipation abrasion loss of the tube according to ISO 4649: 50+5mm3



Item Code	Dash Size	ID		OD		WP		BP		W
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m
PH684-08	-08	1/2	12.7	1.18	30.0	175	12	525	36	0.75
PH684-12	-12	3/4	19.0	1.50	38.0	175	12	525	36	1.10
PH684-16	-16	1	25.0	1.89	48.0	175	12	525	36	1.60
PH684-20	-20	1.1/4	32.0	2.17	55.0	175	12	525	36	1.90
PH684-24	-24	1.1/2	38.0	2.40	61.0	175	12	525	36	2.15
PH684-32	-32	2	51.0	2.87	73.0	175	12	525	36	2.65



Temperature Range : Continuous: -30°C to +70°C