

PH684 - SHOT BLASTING HOSE W.P. 12 BAR

Construction

Inner tube Black Colour, Synthetic and natural rubber blend resistant to abrasion

Reinforcement Four Plies of synthetic textile cords with two cross anti static copper wires

Cover Black colour, Synthetic rubber resistant to ozone, weather and abrasion

Application Suitably designed long lasting heavy duty hose for use in sand, metal grits and foundry waste with

conductive rubber compound to ensure static electricity dissipation abrasion loss of the tube

according to ISO 4649: 50+5mm3

Item Code	Dash Size	ID ID		OD OD		WP		BP		w w
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m
PH684-08	-08	1/2	12.7	1.18	30.0	175	12	525	36	0.75
PH684-12	-12	3/4	19.0	1.50	38.0	175	12	525	36	1.10
PH684-16	-16	1	25.0	1.89	48.0	175	12	525	36	1.60
PH684-20	-20	1.1/4	32.0	2.17	55.0	175	12	525	36	1.90
PH684-24	-24	1.1/2	38.0	2.40	61.0	175	12	525	36	2.15
PH684-32	-32	2	51.0	2.87	73.0	175	12	525	36	2.65



Temperature Range: Continuous: -30°C to +70°C