

PH734 - GREASE HOSE - LOW PRESSURE



Construction

Inner tube Thermoplastic Elastomer

Reinforcement Single Braid of Synthetic fiber

Cover Polyurethane, Black Colour

Application Specially designed for diverse greasing and lubrication applications of the industrial, hand held or automatic (centralized) grease distribution equipments.

| Item Code | Dash Size | DN | ID | | OD | | WP | | BP | | BR/r | | W |
|-----------|-----------|----|------|------|-------|------|------|-----|------|-----|------|----|-----|
| | | | inch | mm | inch | mm | psi | bar | psi | bar | inch | mm | g/m |
| PH734-04 | -04 | 06 | 1/4 | 6.4 | 0.409 | 10.4 | 1523 | 105 | 6090 | 420 | 1.2 | 30 | 70 |
| PH734-05 | -05 | 08 | 5/16 | 8.0 | 0.510 | 13.0 | 1523 | 105 | 6090 | 420 | 1.6 | 40 | 112 |
| PH734-06 | -06 | 10 | 3/8 | 9.5 | 0.551 | 14.0 | 1523 | 105 | 6090 | 420 | 2.0 | 50 | 160 |
| PH734-08 | -08 | 12 | 1/2 | 12.7 | 0.690 | 17.5 | 1523 | 105 | 6090 | 420 | 3.0 | 75 | 200 |



Temperature Range : Continuous: -40°C to +82°C