

PH762 - HYBRID HOSE - 2W



Construction

Inner tube Thermoplastic Elastomer

Reinforcement Two Braids of Steel Wire

Cover Synthetic Rubber, Black Colour

Application High Pressure Hydraulic Lines 165 to 400 bar. For use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural machinery, Earthmoving, material handling equipment and machineries / systems

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH762-04	-04	06	1/4	6.4	0.570	14.5	5800	400	23200	1600	2.0	50	366
PH762-06	-06	10	3/8	9.5	0.680	17.3	4780	330	19200	1320	2.5	64	527
PH762-08	-08	12	1/2	12.7	0.820	20.8	4000	275	16000	1104	3.5	90	660
PH762-10	-10	16	5/8	16.0	0.970	24.6	3620	250	14500	1000	4.0	100	876
PH762-12	-12	20	3/4	19.0	1.100	27.9	3110	215	12440	860	4.8	120	1006
PH762-16	-16	25	1	25.4	1.450	36.8	2390	165	9600	660	6.0	150	1192



Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids