

PH817 - POLY - BITUMEN TRANSFER HOSE

Applicable Standard : EN 13765 Type 2



Construction

Construction

Hose made from polypropylene fabric and films with PVC coated fabric cover, inner & outer galvanised wire and lined with layer of PTFE film

Application

Transferring high temperature viscous fluids(Bitumen and Tar)

Item Code	ID		OD		WP		BR/r		W
	inch	mm	inch	mm	psi	bar	inch	mm	kg/m
PH817-16	1	25	1.26	32	150	10	4.92	125	1.3
PH817-20	1.1/4	32	1.65	42	150	10	5.91	150	1.5
PH817-24	1.1/2	38	2.01	51	150	10	5.91	150	1.7
PH817-32	2	50	2.52	64	150	10	7.87	200	2.2
PH817-40	2.1/2	65	2.99	76	150	10	7.87	200	2.9
PH817-48	3	75	3.62	92	150	10	11	280	3.5
PH817-64	4	100	4.72	120	150	10	15.7	400	5.5
PH817-96	6	150	6.89	175	150	10	22.6	575	12.9
PH817-128	8	200	9.45	240	150	10	31.5	800	17
PH817-160	10	250	12.8	325	150	10	47.2	1200	19.3



Temperature Range : Continuous: -30°C to +150°C

Intermittent : +180°C