

## PH516 - PW 6K - 2 WB



## Construction:

Inner tube: Black colour, Synthetic rubber resistant to hot water

**Reinforcement:** Double steel wire braids

**Cover :** Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone. Available in wrap and smooth finish\*

**Application :** For pressure washer applications with a maximum pressure of 415 Bar. for cold and hot water up to 155 °C

Note: Also Available in Blue and Grey colour Covers on request, Not suitable for steam and oil applications

| Item<br>Code | Dash<br>Size | DN | Ţ <u></u> |     | OD OD |      | WP   |     | BP    |      | BR/r |    | w<br>w |
|--------------|--------------|----|-----------|-----|-------|------|------|-----|-------|------|------|----|--------|
|              |              |    | inch      | mm  | inch  | mm   | psi  | bar | psi   | bar  | inch | mm | kg/m   |
| PH516-04     | -04          | 06 | 1/4       | 6.7 | 0.53  | 13.6 | 6000 | 415 | 18000 | 1245 | 3.0  | 75 | 0.360  |
| PH516-05     | -05          | 08 | 5/16      | 8.2 | 0.60  | 15.3 | 6000 | 415 | 18000 | 1245 | 3.3  | 85 | 0.372  |
| PH516-06     | -06          | 10 | 3/8       | 9.8 | 0.68  | 17.4 | 6000 | 415 | 18000 | 1245 | 3.5  | 90 | 0.449  |



Temperature Range: Continuous: -10°C to +155°C

<sup>\*</sup>Smooth cover available only upto size 1"