

**PH521 - SUPER SERVICE HOSE**

**Applicable Standard :** Exceeds EN 857 - 1SC / EN 1829-2



**Construction :**

**Inner tube :** Black colour, Synthetic rubber resistant to hot water

**Reinforcement :** Single steel wire braid

**Cover :** Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone. Available in wrap and smooth finish\*, Color option in Grey, Blue available on request

**Application :** Cleaning lines for lobby and semi professional machines. High flexibility for use with minerals, glycols, polyglycols oils, synthetic ester oils, oils in water emulsion

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH521-04	-04	06	1/4	6.7	0.47	12.0	5220	360	13050	900	3.0	75	0.195
PH521-05	-05	08	5/16	8.2	0.54	13.6	4930	340	12325	850	3.3	85	0.232
PH521-06	-06	10	3/8	9.8	0.63	16.0	4350	300	10875	750	3.5	90	0.312
PH521-08	-08	12	1/2	13.1	0.78	19.6	3625	250	9065	625	5.1	130	0.428



**Temperature Range :** Continuous: -40°C to +155°C

**\*Smooth cover available only upto size 1"**