

PH649 - CONCRETE DELIVERY HOSE



Construction :

Inner tube : Black colour, Synthetic and natural rubber blend resistant to abrasion

Reinforcement : Plies of synthetic textile cords with two cross anti static copper wires

Cover : Black colour, Synthetic rubber resistant to ozone, weather and abrasion

Application : Designed for concrete pumping in construction industry

Item Code	Dash Size	ID		OD		WP		BP		W
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m
PH649-20	-20	1.1/4	32.0	1.93	49.0	1235	85	2465	170	1.60
PH649-24	-24	1.1/2	38.0	2.20	56.0	1235	85	2465	170	1.80
PH649-32	-32	2	51.0	2.80	71.0	1235	85	2465	170	3.00
PH649-40	-40	2.1/2	64.0	3.43	87.0	1235	85	2465	170	3.77
PH649-48	-48	3	76.0	4.02	102.0	1235	85	2465	170	4.90
PH649-56	-56	3.1/2	88.0	4.53	115.0	1235	85	2465	170	5.66
PH649-64	-64	4	102.0	5.20	132.0	1235	85	2465	170	7.36
PH649-80	-80	5	127.0	6.18	157.0	1235	85	2465	170	8.92



Temperature Range : Continuous: -30°C to +70°C