

PH341 - PAINT & AGGRESSIVE CHEMICAL SPRAY - 1W



Construction :

Inner tube : PTFE (Polytetrafluoroethylene)

Reinforcement : Single Braid of steel wire

Cover : Polyurethane, Blue Colour, Pin pricked

Application : Airless paint spray systems for 200 to 350 bar. Suitable for applications requiring chemical resistance to solvents and aggressive fluids. Specially suitable for moisture cure adhesives and two components chemicals transfer

Note : Special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH341-03	-03	05	3/16	4.8	0.380	9.7	5000	350	20000	1400	1.2	30	138
PH341-04	-04	06	1/4	6.4	0.460	11.7	4650	320	18600	1280	1.6	40	180
PH341-05	-05	08	5/16	8.0	0.535	13.6	4000	275	16000	1100	2.0	50	220
PH341-06	-06	10	3/8	9.5	0.595	15.1	3600	250	14400	1000	2.4	60	257
PH341-08	-08	12	1/2	12.7	0.725	18.4	2900	200	11600	800	3.0	75	337



Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids