

PH343 - PAINT SPRAY - 2W



Construction :

Inner tube : Polyamide

Reinforcement : Double braids of steel wire

Cover : Polyurethane, Blue Colour, Pin pricking (Optional)

Application : High pressure airless paint spray systems for 150 to 450 bar. Suitable for applications requiring chemical resistance to solvents and aggressive fluids. Due to low permeation value of polyamide, the hose is also suitable for industrial gases

Note : Available Twin & Multi lines with different Hose combination and Size

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH343-04	-04	06	1/4	6.4	0.540	13.7	6500	450	26000	1800	4.0	100	336
PH343-05	-05	08	5/16	8.0	0.600	15.2	5800	400	23200	1600	4.3	110	388
PH343-06	-06	10	3/8	9.5	0.690	17.5	5500	380	22000	1520	5.0	127	483
PH343-08	-08	12	1/2	12.7	0.830	21.1	4350	300	17400	1200	7.0	178	605
PH343-10	-10	16	5/8	16.0	0.975	24.8	3000	210	12000	840	8.0	203	803
PH343-12	-12	20	3/4	19.0	1.125	28.6	2300	160	9200	640	10.0	250	922
PH343-16	-16	25	1	25.4	1.360	34.5	2175	150	8700	600	12.0	305	1092



Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids