

PH347 - SUPER HIGH PRESSURE PAINT SPRAY



Construction :

Inner tube : Polyamide

Reinforcement : One or more Braids of Aramid fiber with single braid of steel wire

Cover : Polyurethane, Blue Colour

Application : Very high pressure Airless paint spray systems for 300 to 700 bar. Suitable for applications requiring chemical resistance to solvents and aggressive fluids

Note : Special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH347-04	-04	06	1/4	6.4	0.540	13.7	10000	700	40000	2800	2.8	70	240
PH347-06	-06	10	3/8	9.5	0.740	18.8	10000	700	40000	2800	4.0	100	381
PH347-08	-08	12	1/2	12.7	0.880	22.4	7500	520	30000	2080	7.1	180	510
PH347-12	-12	20	3/4	19.0	1.150	29.2	5000	345	20000	1380	7.5	191	760
PH347-16	-16	25	1	25.4	1.440	36.6	4350	300	17400	1200	10.0	254	1405



Temperature Range : Continuous: -40°C to +100°C Temp. not to exceed +70°C for Air and Water based fluids